

# Biomass Workshops

## Section 2 – Harvest, Store and Deliver

Paddy Donovan  
Donovan Forestry Services  
Forestry Coordinator Clare Wood Energy Project  
Energy Solutions 7<sup>th</sup> September 2007



---

---

---

---

---


---

---

---

## Harvesting

- Normally is a line and selection
- Harvested material is felled, cross cut into various products and stacked to the side
- Extracted to roadside by a forwarder
- Pulpwood is best stacked in a open area where the wind and sun can dry the logs



---

---

---

---

---

---

---

---

## Storage

To produce good quality chips

- the logs and piles must be kept free from dirt, stones
- raise above the road to avoid splashing and ensure drainage
- sawn ends facing SW
- preferable covered
- the road must be serviceable at all times of the year

---

---

---

---

---

---

---

---

## Storage

The purpose of storage is allow the logs to dry to the required moisture content. This is typically about 45% for a medium sized boiler 200kW to 550kW. Under Irish conditions this will take between 6 and 9 months

Logs stored in the round are easier to handle and transport.

Roundwood will not deteriorate if air can circulate through the storage pile

Chips above 30%MC will deteriorate (compost, reduces energy content) and heat if piled. Piles have been known to catch fire. 3 to 4 weeks storage max at heights less than 3m, will need to be turned (adds to cost)

Health hazard due to fungal spores from wet chip heaps

---

---

---

---

---

---

---

---

## Chipping

**Golden Rule – Not all chippers are the same. Some were designed as fuel wood chippers; others (cheap ones) were not.**

Fuel wood chippers have screens to ensure chip sizes meets standards



---

---

---

---

---

---

---

---



without own chassis to truck



tandem axle chassis to tractor



tandem axle chassis self-propelled (300 hp)



feeding table



changing of the screen



removing of the knives for sharpening

Photos: Kesla Oyj

---

---

---

---

---

---

---

---

## Delivery and on Site Storage

The fuel reception area and its design impacts on the cost of wood fuel.

The delivery system must be;

- Simple
- Accessible
  - Turning space
  - Reception point capable of handling delivery in fast efficient manner
- Flexible accommodate various trailer options
- Store must hold 10 days supply when running at peak



---

---

---

---

---

---

---

---

## Delivery Systems – Bunker Type



Purpose built bunker type fuel store;

Adv.

- Quick delivery
- Most flexible special trailers not required

Dis.

- Expensive to build
- Requires space

---

---

---

---

---

---

---

---

## Delivery Systems – Walking Floor

Walking Floor normally built above ground delivery wagon tips on to floor of the shed

Adv.

- Quick, flexible delivery
- Cheaper than below ground

Dis.

- Construction costs
- Space



---

---

---

---

---

---

---

---

## Delivery – Silos blown storage

Grain type above ground silos.

Adv.

- Cheap to install
- Require small foot print

Dis.

- Can be tied to single supplier
- Slow delivery increases delivery cost



---

---

---

---

---

---

---

---

## Delivery - Bins



Container bins

Adv.

- Cheap to install
- Quick deliveries
- Very clean

Dis.

- Requires special truck but bins can be filled by any chipper.
- Require space

---

---

---

---

---

---

---

---

## Quality – chip size

Various standards in place CEN and Onörm each set the allowed particle size, moisture content, ash fraction and emissions.

Quality Issues -

Chip Size

- Over sized chips will block or bridge an auger
- Dust will extinguish the flame
- Dirt or excessive bark causes problems with emissions
- Gate hangers not acceptable



---

---

---

---

---

---

---

---

## Example - Onörm

Parameter	Measure	G30	G50	G100
Max Cross	cm <sup>2</sup>	3	5	10
Max length	cm	8.5	12	25
Coarse Material 20%	Sieve Mesh	16	31.5	63
Main Material 60 – 100%	Sieve Mesh	2.8	5.6	11.2
Fine Material 20%	Sieve Mesh	1	1	1
Dust 4%	Passing Sieve	1	1	1

---

---

---

---

---

---


---

---

## Quality – Moisture Content

Moisture content and energy yield are closely linked

Boilers will not reach required efficiency if the moisture content of the chips is outside of their range




---

---

---

---

---

---

---

---

## Biomass Workshops

### Section 3 – Example (The Non-Technical Version)

Paddy Donovan  
Donovan Forestry Services  
Forestry Coordinator Clare Wood Energy Project  
Energy Solutions 7<sup>th</sup> September 2007




---

---

---

---

---

---

---

---

## Example

What is the energy yield for a 10ha block of first thinnings;

Area 10ha

DBH 14cm

Yield per ha 70m<sup>3</sup>

Pulpwood = ?m<sup>3</sup> @ 55%MC

Tonnes of woodchips at 40%MC =

Energy Yield = ?kWh

---

---

---

---

---

---

---

---

## Solution – calculate harvested volume

Total Volume: 10ha x 70m<sup>3</sup> = 700m<sup>3</sup>

Pulpwood fraction @ dbh 14cm = 70%

700m<sup>3</sup> x 0.7 = 490m<sup>3</sup>

490m<sup>3</sup> / 1.2 = 408t

---

---

---

---

---

---

---

---

## Solution – Calculate Energy Yield

490m<sup>3</sup> @ 40%MC = ?t

490m<sup>3</sup> / 1.5 = 326t

kWh per t @ 40%MC = ?kWh

326 X 3000 = 978,000kWh

---

---

---

---

---

---

---

---